

TECHNICAL DATA

Fluke BC430 Line Voltage Adapter/Battery Charger



Key features

- Mains (Line Voltage): switchable 115 V ± 15% or 230 V ± 15%
- Equipped with a male receptacle plug that must be connected to a line cord/adapter appropriate for local use. (Line cord/adapter not included)

Product overview: Fluke BC430 Line Voltage Adapter/Battery Charger

Provides power cord operation and charging for Fluke 430 Series Power Quality Analyzers.

Specifications: Fluke BC430 Line Voltage Adapter/Battery Charger

Specifications	
Frequency (all versions)	50...60 Hz ± 10%
Output voltage	17.8 V DC
Output power	15 W
Power consumption	23.7 VA
Max. voltage to ground	600 V CAT IV per IEC 1010-1

Ordering information



Fluke BC430

BC430 Line Voltage Adapter/Battery Charger

Fluke. *Keeping your world up and running.®*

Fluke (UK) Ltd.
52 Hurricane Way
Norwich, Norfolk
NR6 6JB
United Kingdom
Tel.: +44 (0)20 7942 0708
E-mail: cs.uk@fluke.com
www.fluke.com/en-gb

©2022 Fluke Corporation. All rights reserved.
Data subject to alteration without notice.
01/2022

**Modification of this document is not permitted
without written permission from Fluke Corporation.**