

TECHNICAL DATA

Fluke VPS100-R 10:1 Voltage Probe Red 100 MHz (one red)



Key features

For ScopeMeter 90 Series, replaces PM8918 probe series.

- Double insulated voltage probe

Specifications: Fluke VPS100-R 10:1 Voltage Probe Red 100 MHz (one red)

General Specifications	
Attenuation	10x
Bandwidth	100 MHz
Max. input voltage	600 V CAT III, 1000 V CAT II per IEC / EN61010-2-031
Max. Voltage to ground	600 V CAT III, 1000 V CAT II per IEC / EN61010-2-031
Input Resistance	10 Mohm
Input Capacitance	16 pF
Compensation range	10 to 35 pF



Cable Length	1.2 m
BB120 Shielded Banana to BNC Adapter is required to adapt to ScopeMeter 120 Series shielded banana jack inputs.	

Ordering information



Fluke VPS100 R

10:1 Voltage Probe Red 100 MHz (one red)

Each probe set includes:

- 600 V CAT III
- 10:1 Voltage Probe (1 red)
- Hook Clip for Probe Tip (1 red)
- 4-mm Test Probe for Probe (1 red)
- Ground Lead with Hook Clip (1 red)
- Ground Lead with Mini Alligator (1 black)

Fluke. *Keeping your world up and running.®*

Fluke (UK) Ltd.
52 Hurricane Way
Norwich, Norfolk
NR6 6JB
United Kingdom
Tel.: +44 (0)20 7942 0708
E-mail: cs.uk@fluke.com
www.fluke.com

©2021 Fluke Corporation. All rights reserved.
Data subject to alteration without notice.
12/2021

**Modification of this document is not permitted
without written permission from Fluke Corporation.**