

TECHNICAL DATA

Fluke Ti Eyepiece

Key features

- Resolution of 800x480
- 4K and Ultra HD support via HDMI
- HDMI input and output
- Histogram
- Peaking, False Color, Pixel-to-Pixel and Clip Guides

Product overview: Fluke Ti Eyepiece

Compatible with Fluke Infrared Cameras, this electronic viewfinder is ideal for situations when there is glare on the LCD screen, when work conditions require awkward camera angles, or as a second monitor for view by multiple people of what the camera is capturing.

Ordering information

Fluke TI Eyepiece

Electronic viewfinder is compatible with Fluke Ti300, Ti300 PRO, Ti400, Ti400 PRO, Ti450, Ti450 PRO, Ti480, Ti480 PRO and Ti450 SF6 cameras



Preventive maintenance simplified. Rework eliminated.

Save time and improve the reliability of your maintenance data by wirelessly syncing measurements using the Fluke Connect™ system.

- Eliminate data-entry errors by saving measurements directly from the tool and associating them with the work order, report or asset record.
- Maximize uptime and make confident maintenance decisions with data you can trust and trace.
- Access baseline, historical and current measurements by asset.
- Move away from clipboards, notebooks and multiple spreadsheets with a wireless one-step measurement transfer.
- Share your measurement data using ShareLive™ video calls and emails.

Find out more at flukeconnect.com



All trademarks are the property of their respective owners. WiFi or cellular service required to share data. Smartphone, wireless service and data plan not included with purchase. First 5 GB of storage is free. Phone support details can be viewed at fluke.com/phones.

Smart phone wireless service and data plan not included with purchase. Fluke Connect is not available in all countries.

Fluke. Keeping your world up and running.®

Fluke (UK) Ltd.
 52 Hurricane Way
 Norwich, Norfolk
 NR6 6JB
 United Kingdom
 Tel.: +44 (0)20 7942 0708
 E-mail: cs.uk@fluke.com
www.fluke.com

©2021 Fluke Corporation. All rights reserved.
 Data subject to alteration without notice.
 12/2021

Modification of this document is not permitted without written permission from Fluke Corporation.