

## TECHNICAL DATA

# CXT1000 Extreme Hard Case



## Key features

- Innovative features for unmatched strength and durability
- Offers maximum protection for your Fluke tools and accessories against high impact, vibration or shock
- O-ring sealed, waterproof up to a depth of 3 feet
- Airtight, and built to withstand the most extreme conditions
- Great for airline travel with an automatic pressure equalization valve for changes in atmospheric pressure
- Spring-release patent pending latches lock in place
- Lock holders are great for use with pad locks for added security
- Customizable, 2-piece sheeted foam offers an extremely tailored, custom fit for your Fluke tools and accessories
- Stackable, finger groove on each side for easy pick up and carry
- Lifetime warranty on the case shell
- IP67 rated
- RoHS compliant

## Product overview: CXT1000 Extreme Hard Case

The CXT1000 is a hard case that fits all your Fluke test tools and accessories. Configure the diced foam interior to store, protect, and carry your test tools.

## Specifications: CXT1000 Extreme Hard Case

### Specifications



Dimensions (HxWxD)	13.5 in x 18.3 in x 7 in (34.3 cm x 46.5 cm x 17.8 cm)
Waterproof depth	0.9 m (3 ft)
Safety certifications	IP67 rated RoHS compliant
Warranty	Lifetime warranty on the case shell

## Ordering information



### **CXT1000**

Extreme Hard Case with do-it-yourself custom foam inserts.

---

**Fluke.** *Keeping your world up and running.®*

**Fluke Corporation**

PO Box 9090, Everett, WA 98206 U.S.A.

**For more information call:**

In the U.S.A. (800) 443-5853

In Europe/M-East/Africa +31 (0)40 267 5100

In Canada (800)-36-FLUKE

From other countries +1 (425) 446-5500

**Fluke Electronics (Malaysia) Sdn Bhd**

Suite D-3A-4, Block D

SouthGage Commercial Centre, No2

Jalan Dua Off Jln Chan Sow Lin

55200 KL

Malaysia

Email: [info.asean@fluke.com](mailto:info.asean@fluke.com)

[www.fluke.com/my](http://www.fluke.com/my)

©2021 Fluke Corporation. Specifications subject to change without notice.

12/2021

**Modification of this document is not permitted without written permission from Fluke Corporation.**