

Wide Angle Infrared Lens



Product overview: Wide Angle Infrared Lens

Wide field of view for inspection of large objects – compatible with TiX1000, TiX660 and TiX640 models.

Applications: Entire wall or side of building or the need to work in tight spaces.

Specifications: Wide Angle Infrared Lens

| General Characteristics | |
|-------------------------|-----------------|
| Lens description | Wide-angle lens |
| Focal distance | 15 mm |
| Focus | 0.47 mm |
| 1024 x 768 | |
| iFOV | 1.1 mRad |
| FOV | 68.7 x 50.7° |
| 640 x 480 | |
| iFOV | 1.7 mRad |
| FOV | 62.3 x 46.4° |

Ordering information



FLK-Xlens/Wide

Applications: Entire wall or side of building or the need to work in tight spaces.
Compatible with TiX1000, TiX660 and TiX640 infrared cameras.



Fluke. *Keeping your world up and running.®*

Fluke Corporation
PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:
In the U.S.A. (800) 443-5853
In Canada (800) 36-FLUKE
From other countries +1 (425) 446-5500
www.fluke.com

©2021 Fluke Corporation.
Specifications subject to change without notice.
12/2021

**Modification of this document is not permitted
without written permission from Fluke Corporation.**