

TECHNICAL DATA

Super Wide Angle Infrared Lens



Product overview: Super Wide Angle Infrared Lens

For extreme wide field of view – compatible with TiX1000, TiX660 and TiX640 models.

Applications: Building facade inspections, surveillance and special R&D applications.

Specifications: Super Wide Angle Infrared Lens

General Characteristics	
Lens description	Super wide-angle lens
Focal distance	7.5 mm
Focus	0.17 mm
1024 x 768	
iFOV	2.3 mRad
FOV	135.8 x 104.4°
640 x 480	
iFOV	3.3 mRad
FOV	128.9 x 92.7°

Ordering information



FLK-Xlens/Sup-Wide

Applications: Building facade inspections, surveillance and special R&D applications.
Compatible with TiX1000, TiX660 and TiX640 infrared cameras.

Fluke. *Keeping your world up and running.®*

Fluke Corporation

PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:

In the U.S.A. (800) 443-5853

In Europe/M-East/Africa

+31 (0)40 267 5100

In Canada (905) 890-7600

From other countries +1 (425) 446-5500

Representative office of Fluke South East Asia Pte Ltd

C/O Danaher Vietnam

Green Power Tower, 11th Floor Unit 2

35 Ton Duch Thang Street, District 1

Ho Chi Minh City

Vietnam

Tel: +84-8-2220-5371 (ext 103)

Email: info.asean@fluke.com

www.fluke.com/vn-vi

©2021 Fluke Corporation. Specifications subject to change without notice.

12/2021

Modification of this document is not permitted without written permission from Fluke Corporation.