

Technische gegevens

Fluke AC175 Alligator Clip Set



Belangrijkste kenmerken

Insulated alligator clips with flexible boots

Threaded shaft to twist onto test probes

Jaw opening: 7 mm (0.275 in)

Jaw contact material: nickel-plated steel

Productoverzicht: Fluke AC175 Alligator Clip Set

Modular clips are used with modular test leads to offer additional flexibility to configure your leads to your individual needs. The insulated alligator clip jaws provide a 7 mm opening with flexible boots.

The Fluke AC175 Threaded Alligator Clip Set comes with a one-year warranty and a cat rating of CAT III 1000 V, CAT IV 600 V, 10 A.

This alligator clip set has slide-on alligator clips (red, black) compatible with multiple Fluke test probes:

Fluke TL71 Premium Test Lead Set

Fluke TL75 Hard Point™ Test Lead Set

Fluke TL175 TwistGuard™ Test Leads

Specificaties: Fluke AC175 Alligator Clip Set

Jaw opening	7 mm (0.275 in), jaw contact material: nickel-plated steel
Category Rating	CAT III 1000 V, CAT IV 600 V, 10 A
Operating temperature	-20°C to 55°C (-4°F to 131°F)
Environmental Information	Pollution Degree 2, 2000 m altitude

Modellen



Fluke AC175

AC175 Alligator Clip Set

Optional accessories	Description
TL71 Meetsnoerenet	Comfort grip, silicone insulated. μ V measurement recommended.
TL175 TwistGuard™-meetsnoeren	Gepatenteerde verlengbare isolatie van de meetpen die voldoet aan de nieuwe elektrotechnische veiligheidseisen, ter verkleining van het blanke meetpengedeelte en voor de benodigde veelzijdigheid voor de meeste metingen
Fluke TP175 TwistGuard™-meetprobes	De Fluke TP175 TwistGuard®-meetprobes hebben instelbare penlengtes waarmee u veilig in verschillende omgevingen kunt werken.
TL75 Hard Point-meetsnoerenet	1 paar (rood, zwart) meetsnoeren met comfort grip, PVC-isolatie en geïsoleerde haakse banaanstekers

Fluke. *Keeping your world up and running.*®

Fluke Belgium N.V.
Kortrijksesteenweg 1095
B9051 Gent
Belgium
Tel: +32 2402 2100
E-mail: cs.be@fluke.com
www.fluke.be

©2022 Fluke Corporation. Alle rechten
voorbehouden.
Wijzigingen zonder voorafgaande kennisgeving
voorbehouden.
01/2022

**Wijziging van dit document is niet toegestaan
zonder schriftelijke toestemming van Fluke
Corporation.**