

Dados técnicos

Fluke Calibration 9102 Handheld Dry-Well



Principais recursos

World's smallest, lightest and most portable dry-wells

- Smallest dry-wells in the world
- Ranges from -10°C to 122°C
- Accuracy to $\pm 0.25^{\circ}\text{C}$, stability of $\pm 0.05^{\circ}\text{C}$
- RS-232 interface
- Fluke Calibration's line of portable dry-wells is incredible. They're the smallest, lightest, and most portable dry-wells in the world. And now they're better than ever!

Informações gerais sobre o produto: Fluke Calibration 9102 Handheld Dry-Well

9102S Dry-Well

For work in the temperature range of -10°C to 122°C , 9102S dry-well is another first in the industry, featuring stability to $\pm 0.05^{\circ}\text{C}$.

This dry-well is only four inches high and six inches wide, achieves temperatures as low as -10°C , includes a NIST-traceable calibration, and is stable to $\pm 0.05^{\circ}\text{C}$. The Model 9102S is excellent for dial gauges, digital thermometers, bulb switches, and other sensors that need calibration below ambient.

The 9102S has two wells so you can use one for a reference thermometer to increase accuracy. Both wells are 1/2 inch in

diameter, and each has inserts available for almost any sensor size. The 9102S also has a battery pack option that gives you approximately four hours of field use when AC power is unavailable.

Especificações: Fluke Calibration 9102 Handheld Dry-Well

| Specifications | 9100S | 9102S |
|-----------------------------------|---|---|
| Range | 35 °C to 375 °C (95 °F to 707 °F) | -10 °C to 122 °C (14 °F to 252 °F) at 23 °C ambient |
| Accuracy | ± 0.25 °C at 50 °C; ± 0.25 °C at 100 °C; ± 0.5 °C at 375 °C | ± 0.25 °C |
| Stability | ± 0.07 °C at 50 °C; ± 0.1 °C at 100 °C; ± 0.3 °C at 375 °C | ± 0.05 °C |
| Well-to-Well Uniformity | ± 0.2 °C with sensors of similar size at equal depths within wells | |
| Heating Times | 35 °C to 375 °C: 9.5 minutes | ambient to 100 °C: 10 minutes |
| Stabilization | 5 minutes | 7 minutes |
| Cooling Times | 375 °C to 100 °C: 14 minutes | ambient to 0 °C: 10 minutes |
| Well Depth | 102 mm (4 in); 1.6 mm (1/16 in) hole is 89 mm (3.5 in) deep | 102 mm (4 in) |
| Removable Inserts | N/A | Available in sizes from 1.6 mm (1/16 in) to 11.1 mm (7/16 in) [6.4 mm (1/4 in) and 4.8 mm (3/16 in) included] |
| Power | 115 V ac (± 10 %), 55–65 Hz, 1.5 A or 230 V ac (± 10 %), 0.8 A, 45–55 Hz, 175 W | 94–234 V ac (± 10 %), 50/60 Hz, 60 W; or 12 VDC |
| Size (HxWxD) | 57 x 125 x 150 mm (2.25 x 4.9 x 6.1 in) | 99 x 140 x 175 mm (3.9 x 5.5 x 6.9 in) |
| Weight | 1 kg (2 lb 3 oz) | 1.8 kg (4 lb) |
| Computer Interface | RS-232 included | |
| NIST-Traceable Calibration | Data at 50 °C, 100 °C, 150 °C, 200 °C, 250 °C, 300 °C, and 375 °C | Data at -10 °C, 0 °C, 25 °C, 50 °C, 75 °C, 100 °C, and 122 °C |

Modelos



9102S

9102S-156, DRY-WELL, HH LOW-TEMP

HDRC Handheld Dry-Well

Fluke. *Keeping your world up and running.®*

Fluke Corporation
PO Box 9090, Everett, WA 98206 EUA

Para obter mais informações, ligue para os seguintes números:

Tel: (11) 3530-8901
Email: info@fluke.com.br
www.fluke.com/pt-br

Fluke do Brasil Ltda
CENESP Av. Maria Coelho Aguiar,
215 – Bloco G, 1º andar
São Paulo/SP – CEP: 05804-900

©2021 Fluke Corporation. Todos os direitos reservados. Os dados fornecidos estão sujeitos a alterações sem aviso prévio.
12/2021

É proibido modificar este documento sem permissão escrita da Fluke Corporation.