

Tekniska data

Fluke 922 Airflow Meter/Kit



Nyckelfunktioner

Fluke 922 was designed and built for how (and where) you do your job, with performance, ruggedness and ease of use, setting the Fluke 922 apart from the competition. The bright white display and ruggedized holster and wrist strap let you take the Fluke 922 into less than ideal environments. The color-coded hoses help you keep track of where your readings are coming from. The simple, intuitive interface means you can measure pressure, velocity, or airflow at the push of a button. The Fluke 922 helps you analyze airflow. Easily.

- Powerful meter provides differential and static pressure, air velocity and flow readings
- Convenient colored hoses help proper interpretation of pressure readings
- Easy to use without sacrificing performance
- Bright, backlit display for clear viewing in all environments
- User-defined duct shape and size for maximum airflow accuracy
- Resolution down to 0.001 in H₂O
- 99 point data storage capacity
- Min/Max/Average/Hold functions for easy data analysis
- Auto power off saves battery life

Produktöversikt: Fluke 922 Airflow Meter/Kit

Analyze airflow. Easily. The 922 Micromanometer.

Today's HVAC technicians want a simple solution for diagnosing ventilation issues. Differential pressure measurements only tell part of the story. Technicians also want to measure air velocity and flow, without having to resort to expensive, difficult to use, specialist tools. The Fluke 922 makes airflow measurements easy by combining three tools: differential pressure,

airflow, and velocity into a single, rugged meter.

Use the Fluke 922 micromanometer to:

- Measure pressure drops across key HVAC equipment to drive peak performance and extend equipment life
- Match ventilation to occupant loads
- Monitor indoor vs. outdoor pressure relationships and manage the building envelope
- Promote indoor comfort and quality
- Perform duct traversals for accurate airflow readings

Specifikationer: Fluke 922 Airflow Meter/Kit

| Technical Specifications | | |
|---------------------------|----------------------------------|---|
| Air pressure | Range / Resolution / Accuracy | ±4000 Pascals / 1 Pascal / ±1% + 1 Pascal |
| | | ±16 inH ₂ O/ 0.001 inH ₂ O/±1% + 0.01 inH ₂ O |
| | | ±400 mmH ₂ O/ 0.1 mmH ₂ O / ±1% + 0.1 mmH ₂ O |
| | | ±40 mbar /0.01 mbar / ±1% + 0.01 mbar |
| | | ±0.6 psi / 0.0001 psi /±1% + 0.0001 psi |
| Air velocity | Range / Resolution / Accuracy | 250 to 16,000 fpm / 1 fpm / ±2.5% of reading at 2000 fpm (10.00 m/s) |
| | | 1 to 80 m/s / 0.001 m/s / ±2.5% of reading at 2000 fpm (10.00 m/s) |
| Air flow (volume) | Range / Resolution / Accuracy | 0 to 99,999 cfm / 1 cfm / Accuracy is a function of velocity and duct size |
| | | 0 to 99,999 / 1 m ³ /hr / Accuracy is a function of velocity and duct size |
| | | 0 to 99,999 l/s / 1 l/s / Accuracy is a function of velocity and duct size |
| Temperature | Range / Resolution / Accuracy | 0°C to 50°C / ±1% + 2°C / 0.1°C |
| | | 32°F to 122°F / ±1% + 4°F / 0.1°F |
| General Specifications | | |
| Operating temperature | 0°C to +50°C (+32°F to +122°F) | |
| Storage temperature | -40°C to +60°C (-40°F to +140°F) | |
| Relative humidity | 0% to 90%, non-condensing | |
| IP rating | IP40 | |
| Operating altitude | 2000 m | |
| Storage altitude | 12000 m | |
| EMI, RFI, EMC | Meets requirements for EN61326-1 | |
| Vibration | MIL-PREF-28800F, Class 3 | |
| Max pressure at each port | 10 psi | |
| Data storage capacity | 99 readings | |



| | |
|---------------------|--|
| Warranty | 2 years |
| Power, battery life | Four AA batteries |
| Battery life | 280 hours without backlight, 60 hours with backlight |

Modeller



Fluke-922/KIT

Fluke. *Keeping your world up and running.*®

Fluke Sverige AB
c/o Gilbarco Veeder-Root
Johannesfredsvägen 11 A
16869 Bromma
Tel: 08 5663 7400
E-mail: cs.se@fluke.com
www.fluke.se

©2021 Fluke Corporation. Med ensamrätt. Data kan komma att ändras utan föregående meddelande. 12/2021

Ändringar får inte göras i det här dokumentet utan skriftligt medgivande från Fluke Corporation.