

# Fluke ITP120 Optically Isolated External Trigger Probe



## คุณลักษณะสำคัญ

- **Input impedance:** 10MΩ in parallel with 15pF.
- **Trigger level:** TTL compatible (High = 2V, Low = 0.8V)
- **Minimum pulsewidth:** 7 μs
- **Maximum frequency:** 50 kHz
- **Maximum signal voltage:** 600 Vrms, CAT II per IEC1010-2-031
- **Maximum voltage to ground:** 600 Vrms, CAT II per IEC1010-2-031
- **Battery type:** Alkaline 9 volt, NEDA, IEC6LR61
- **Battery life:** 60 hours

## ภาพรวมผลิตภัณฑ์: Fluke ITP120 Optically Isolated External Trigger Probe

Designed for use with Fluke ScopeMeter 120-series. The probe connects to the optical port of the ScopeMeter 120, and features isolated external triggering, for measurements that require external triggering or triggering on floating reference signals. Probe length is 1.2m (48 inch). The probe includes a hookclip with ground lead, and a 9-Volt Alkaline battery.

- **Input impedance:** 10MΩ in parallel with 15pF.
- **Trigger level:** TTL compatible (High = 2V, Low = 0.8V)
- **Minimum pulsewidth:** 7 μs
- **Maximum frequency:** 50 kHz
- **Maximum signal voltage:** 600 Vrms, CAT II per IEC1010-2-031
- **Maximum voltage to ground:** 600 Vrms, CAT II per IEC1010-2-031
- **Battery type:** Alkaline 9 volt, NEDA, IEC6LR61

- Battery life: 60 hours

**รุ่น****Fluke ITP120**Optically Isolated External Trigger Probe

---

**Fluke. ให้โลกของคุณ คงอยู่แต่ละก้าวต่อไป**

Fluke Corporation  
PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:  
In the U.S.A. (800) 443-5853  
In Europe/M-East/Africa  
+31 (0)40 267 5100  
In Canada (800)-36-FLUKE  
From other countries +1 (425) 446-5500  
[www.fluke.com/th-th](http://www.fluke.com/th-th)

©2021 Fluke Corporation. Specifications subject to  
change without notice.  
12/2021

Modification of this document is not permitted without  
written permission from Fluke Corporation.